



WIDESCAPE

WS250

The original stand-up snowmobile
More versatility. More fun.

MSRP \$8,499 + tax
(includes shipping & handling)

UP-THE-RIDE



HIGHLIGHTS

- ▶ Widescape's custom-built 242cc WS250® engine. Compact, lightweight, fuel-efficient, and extremely durable for high reliability in all conditions.
- ▶ Direct-drive CVT drivetrain made by CVTech®, ensuring a smooth and responsive power output every time you press on the throttle.
- ▶ Solid and lightweight aluminum chassis and frame for a super floatable and maneuverable ride.
- ▶ Non-slip traction mat with snow-clearing grooves.
- ▶ High-performance front and rear suspension for a smooth and agile driving experience.
- ▶ Thumb-operated throttle for ease and comfort.
- ▶ Custom designed scaled track, engineered and crafted by Soucy® with 1.5 in. lugs for optimal traction and control.
- ▶ Custom designed ski, manufactured by PPD®. Equipped with a single central keel and dual-side runners to ensure optimal grip and precise handling.
- ▶ Light and compact bodywork made with HDPE plastics that resist shocks and cold 4 in. digital display that give you all the info you need while you ride: low/high oil temperature, low battery voltage, check engine, odometer, tripmeter, clock.=

WS250® ENGINE

| | |
|--------------------------|--|
| Engine details | Liquid-cooled, four-stroke |
| Torque | 22 N*m (16 ft-lbs) |
| Cylinders / Displacement | 1 / 242 cc |
| Valves | 2 |
| Bore / Stroke | 71 mm x 61 mm (2.79 in. x 2.40 in.) |
| Carburation | Electronic Fuel Injection (EFI) |
| Fuel Type / Octane | Premium unleaded recommended / 86 |
| Fuel Tank | 8 L (2.11 US gal) |
| Driving mode | Integrated dual power curve: Standard mode and Woods mode |

DRIVETRAIN

| | |
|----------------------|---------|
| Drive clutch | CVTech® |
| Drive sprocket ratio | 0.326 |

DRY WEIGHT

Dry weight 91 kg (200 lb)

DIMENSIONS

| | |
|-------------------------------------|---|
| Overall vehicle length | 2,200 mm (86.4 in.) |
| Overall vehicle width | 800 mm (31.44 in.) |
| Overall vehicle height | 1,300 mm (51.12 in.) |
| Ski stance | 305 mm (12 in.) |
| Track (Length x Width x Profile) | 2,667 mm x 305 mm x 38 mm (105 in. x 12 in. x 1.5 in.) |

SUSPENSION

| | |
|-------------------------|-------------------|
| Front suspension | Widescape® design |
| Front suspension travel | 140 mm (5.51 in.) |
| Rear suspension | Widescape® design |
| Rear suspension travel | 100 mm (3.93 in.) |

FEATURES

| | |
|--------------------|--|
| Frame | Aluminium |
| Bodywork | HDPE and LDPE materials; optimized integration with aluminum framing parts |
| Ski | UHMW material; optimized with track stand, single keel and dual-side metal lips |
| Handlebar | Aluminum material Width : 780 mm (30.70 po) Diameter : 35 mm (1.37 po) Rise : 15 mm (0.59 po) |
| Riser block height | 30 mm (1.18 in.) height adjustment |
| Starter | Electric |
| Brake system | J.Juan® floating caliper system |
| Heated grips | Optional |
| Digital display | 100 mm (4 in.) |